


**PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR T5/140W (UVC GERMICIDAL) LAMP (FOR MODEL:TUV 64T5 HO 4P SE, PHILIPS)**

**MODEL DESCRIPTION:**



Ballast Body Type: UV5  
LAMP:T5/140W/UVC  
Cap: 4P/SE (FOUR PINS, SINGLE ENDED)  
LAMP MAKE: PH (PHILIPS)



UV5: DIMENSION: L=278mm, W=55mm, H=42mm

**TECHNICAL SPECIFICATIONS:**

- TYPE: UV ELECTRONIC BALLAST/INDUSTRIAL FOR T5/140W, 4P, SE
- BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE
- OPERATING VOLTAGE RANGE:  $U_n = 170\text{Vac} - 300\text{Vac}$
- MAINS RATED VOLTAGE:  $V=230\text{Vac}$
- MAINS FREQUENCY:  $F_n(\text{Hz})=50\text{Hz}$
- MAINS I/P CURRENT:  $I_n=640\text{mA}$
- WATTAGE: 140W
- POWER FACTOR:  $PF > 0.95$
- SURGE PROTECTION DEVICE:  $SPD > 10\text{KV}$
- CREST FACTOR:  $CF > 1.70$
- AMBIENT TEMPERATURE:  $T_a=0...50^\circ\text{C}(\text{max})$
- CASE TEMPERATURE:  $T_c=60^\circ\text{C}(\text{max})$
- TOLERANCE:  $\pm 5\%$
- IN RUSH CURRENT & RFI/EMI PROTECTION



**FEATURES:**

- SLIM DESIGN
- BODY:METALLIC POWDER COATED
- MAINS LED INDICATOR:RED
- O/P GREEN LED INDICATOR SIGNIFIES HEALTHY LAMP/TUBE
- O/P RED INDICATOR BLINKS WHEN LAMP/TUBE IS UNHEALTHY
- O/P BUZZER BEEPS WHEN LAMP/TUBE IS UNHEALTHY

**\*Due to continuous R&D, design can be changed without prior notification**

**\*Special Requirements will be entertained**

**WORKS/FACORY ADDRESS:**

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura,opp. Suprabhat Industrial Estate,  
O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com,mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com