





PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR 127W (AMALGAM UVC GERMICIDAL) LAMP (FOR MODEL: UV5-GPHA1000 T5 127W,LIGHT SOURCES)

MODEL DESCRIPTION:

- Ballast Body Type: UV5
- Lamp Type: GPHA (Preheat Start Amalgam UVC Lamp)
- Lamp Length: 1000mm
- Lamp:T5/127W
- Cap: 4P-SE (Four Pins, Single Ended), G5(Single Sided Bi Pin)
- Make: LIGHT SOURCES





FOR G5



UV5: DIMENSION: L=278mm, W=55mm, H=42mm

TECHNICAL SPECIFICATIONS:

- TYPE: UV ELECTRONIC BALLAST/INDUSTRIAL FOR AMALGAM UVC LAMP, G5 OR 4P-SE
- BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE
- OPERATING VOLTAGE RANGE: $U_n = 170\text{Vac} - 300\text{Vac}$
- MAINS RATED VOLTAGE: $V=230\text{Vac}$
- MAINS FREQUENCY: $F_n(\text{Hz})=50\text{Hz}$
- MAINS I/P CURRENT: $I_n=580\text{mA}$
- WATTAGE: 127W
- POWER FACTOR: $PF > 0.95$
- SURGE PROTECTION DEVICE: $SPD > 10\text{KV}$
- CREST FACTOR: $CF > 1.70$
- AMBIENT TEMPERATURE: $T_a=0\text{...}50^\circ\text{C}(\text{max})$
- CASE TEMPERATURE: $T_c=60^\circ\text{C}(\text{max})$
- TOLERANCE: $\pm 5\%$
- IN RUSH CURRENT PROTECTION
- RFI/EMI PROTECTION



FEATURES:

- SLIM DESIGN
- BODY:METALLIC POWDER COATED
- MAINS LED INDICATOR: RED
- O/P GREEN LED INDICATOR SIGNIFIES HEALTHY LAMP/TUBE
- O/P RED INDICATOR BLINKS WHEN LAMP/TUBE IS UNHEALTHY
- O/P BUZZER BEEPS WHEN LAMP/TUBE IS UNHEALTHY

***Due to continuous R&D, design can be changed without prior notification**

***Special Requirements will be entertained**

WORKS/FACORY ADDRESS:

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,
O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com
www.vision-techs.com, www.visiontechled.com