





**PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR  
2XT5/79W/UVC LAMP (FOR MODEL: UV5-G67T5/79W, LIGHT SOURCES)**

**MODEL DESCRIPTION:**


Ballast Body Type: UV5  
Lamp Type: Instant Start  
Lamp:T5/79W(QUARTZ UVC LAMP)  
Cap: G5 or 4P-SE (Four Pins, Single Ended)  
Make: LIGHT SOURCES



UV5: DIMENSION: L=278mm, W=55mm, H=42mm


**TECHNICAL SPECIFICATIONS:**

- TYPE: UVC ELECTRONIC BALLAST/INDUSTRIAL
- BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE
- OPERATING VOLTAGE RANGE:  $U_n = 170V_{ac} - 300V_{ac}$
- MAINS RATED VOLTAGE:  $V=230V_{ac}$
- MAINS FREQUENCY:  $F_n(Hz)=50Hz$
- MAINS I/P CURRENT:  $I_n=725mA$
- WATTAGE: 158W
- POWER FACTOR:  $PF > 0.95$
- SURGE PROTECTION DEVICE:  $SPD > 10KV$
- CREST FACTOR:  $CF > 1.70$
- AMBIENT TEMPERATURE:  $T_a=0...50^{\circ}C(max)$ , CASE TEMPERATURE:  $T_c=60^{\circ}C(max)$
- TOLERANCE:  $\pm 5\%$
- IN RUSH CURRENT PROTECTION, RFI/EMI PROTECTION



**FEATURES:**

- SLIM DESIGN
- BODY:METALLIC POWDER COATED
- MAINS LED INDICATOR:RED
- O/P GREEN LED INDICATORS SIGNIFY HEALTHY LAMPS/TUBES



**\*Due to continuous R&D, design can be changed without prior notification**

**\*Special Requirements will be entertained**

**WORKS/FACORY ADDRESS:**

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,

O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com