

An ISO 9001:2015 Certified Co.



**VISION TECH<sup>®</sup>**  
**ELECTRONICS**



**PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR 95W (HIGH O/P UVC GERMICIDAL) LAMP (FOR MODEL: UV4-GH0893T5 95W, LIGHT SOURCES**

**MODEL DESCRIPTION:**


Ballast Body Type: UV4

Lamp:T5/95W (High O/P Quartz Germicidal Lamp)


Lamp Length:893mm

Cap: 4P-SE (Four Pins, Single Ended), G5(Single Sided Bi Pin)

Make: LIGHT SOURCES





4P-SE



UV4: DIMENSION: L=320mm, W=40mm, H=35mm

**TECHNICAL SPECIFICATIONS:**

- TYPE: UV ELECTRONIC BALLAST/INDUSTRIAL FOR HIGH O/P UVC, T5 95W, G5 OR 4P-SE
- BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE
- OPERATING VOLTAGE RANGE:  $U_n = 170V_{ac} - 300V_{ac}$
- MAINS RATED VOLTAGE:  $V=230V_{ac}$
- MAINS FREQUENCY:  $F_n(Hz)=50Hz$
- MAINS I/P CURRENT:  $I_n=435mA$
- WATTAGE: 95W
- POWER FACTOR:  $PF > 0.95$
- SURGE PROTECTION DEVICE:  $SPD > 10KV$
- CREST FACTOR:  $CF > 1.70$
- AMBIENT TEMPERATURE:  $T_a=0...50^{\circ}C(max)$
- CASE TEMPERATURE:  $T_c=60^{\circ}C(max)$
- TOLERANCE:  $\pm 5\%$
- IN RUSH CURRENT AND RFI/EMI PROTECTION



**FEATURES:**

- SLIM DESIGN
- BODY: METALLIC POWDER COATED
- MAINS LED INDICATOR: RED
- O/P GREEN LED INDICATOR SIGNIFIES HEALTHY LAMP/TUBE
- O/P RED INDICATOR BLINKS WHEN LAMP/TUBE IS UNHEALTHY
- O/P BUZZER BEEPS WHEN LAMP/TUBE IS UNHEALTHY

\*Due to continuous R&D, design can be changed without prior notification

\*Special Requirements will be entertained

**WORKS/FACORY ADDRESS:**

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,

O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com