



An ISO 9001:2015 Certified Co.




VISION TECH[®]
ELECTRONICS



PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR 2XT8/30W (SOFT GLASS UVC) LAMP (FOR MODEL: UV3-LTC30T8 30W, LIGHT SOURCES)

MODEL DESCRIPTION:

Ballast Body Type: UV3
Lamp:T8/30W (SOFT GLASS UVC GERMICIDAL LAMP)
Cap: MDBP (Medium Bi-Pin)
Make: LIGHT SOURCES





UV3: DIMENSION: L=263mm, W=39mm, H=32mm

TECHNICAL SPECIFICATIONS:

- TYPE: UVC ELECTRONIC BALLAST/INDUSTRIAL
- BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE
- OPERATING VOLTAGE RANGE: $U_n = 170\text{Vac} - 300\text{Vac}$
- MAINS RATED VOLTAGE: $V=230\text{Vac}$
- MAINS FREQUENCY: $F_n(\text{Hz})=50\text{Hz}$
- MAINS I/P CURRENT: $I_n=275\text{mA}$
- WATTAGE: 60W
- POWER FACTOR: $PF > 0.95$
- SURGE PROTECTION DEVICE: $SPD > 10\text{KV}$
- CREST FACTOR: $CF > 1.70$
- AMBIENT TEMPERATURE: $T_a=0 \dots 50 \text{ C}(\text{max})$,
- CASE TEMPERATURE: $T_c=50 \text{ C}(\text{max})$
- TOLERANCE: $\pm 5\%$
- IN RUSH CURRENT PROTECTION, RFI/EMI PROTECTION

FEATURES:

- SLIM DESIGN
- BODY: METALLIC POWDER COATED
- MAINS LED INDICATOR: RED
- O/P GREEN LED INDICATORS SIGNIFY HEALTHY LAMPS/TUBES



***Due to continuous R&D, design can be changed without prior notification**

***Special Requirements will be entertained**

WORKS/FACTORY ADDRESS:

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,

O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com