

An ISO 9001:2015 Certified Co.



VISION TECH[®]
ELECTRONICS



PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR

2X60W, Compact Soft Glass High Power HO UVC Germicidal Lamp

(FOR MODEL: UV5-LTC60W/HO 2G11 60W)


MODEL DESCRIPTION:

Ballast Body Type: UV5

LAMP: 60W, Compact Soft Glass High Power Germicidal Lamp

Cap: 2G11

Make: LIGHT SOURCES



UV5: DIMENSION: L=278mm, W=55mm, H=42mm

TECHNICAL SPECIFICATIONS:

-TYPE: COMPACT UVC ELECTRONIC BALLAST/INDUSTRIAL

-BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE

-OPERATING VOLTAGE RANGE: $U_n = 170\text{Vac} - 300\text{Vac}$

-MAINS RATED VOLTAGE: $V = 230\text{Vac}$

-MAINS FREQUENCY: $F_n(\text{Hz}) = 50\text{Hz}$

-MAINS I/P CURRENT: $I_n = 550\text{mA}$

-WATTAGE: 120W

-POWER FACTOR: $PF > 0.95$

-SURGE PROTECTION DEVICE: $SPD > 10\text{KV}$

-CREST FACTOR: $CF > 1.70$

-AMBIENT TEMPERATURE: $T_a = 0 \dots 50^\circ\text{C}(\text{max})$, CASE TEMPERATURE: $T_c = 60^\circ\text{C}(\text{max})$

-TOLERANCE: $\pm 5\%$

-IN RUSH CURRENT PROTECTION, RFI/EMI PROTECTION


FEATURES:

-SLIM DESIGN

-BODY: METALLIC POWDER COATED

-MAINS LED INDICATOR: RED

-O/P GREEN LED INDICATORS SIGNIFY HEALTHY LAMPS/TUBES



***Due to continuous R&D, design can be changed without prior notification**

***Special Requirements will be entertained**

WORKS/FACORY ADDRESS:

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,

O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com