

An ISO 9001:2015 Certified Co.



VISION TECH[®]
ELECTRONICS



PARAMETERS/TECHNICAL SPECIFICATIONS OF ELECTRONIC BALLAST FOR

2X60W (HIGH O/P UVC GERMICIDAL, H-SHAPE) LAMP (FOR MODEL: UV5-GHO60T5/H, 2G11-ARKLITE)

MODEL DESCRIPTION:


Ballast Body Type: UV5

Lamp Type: Preheat Start,

Lamp: High O/P UVC Germicidal, H-Shape Lamp

Cap: 2G11


Make: ARKLITE



UV5: DIMENSION: L=278mm, W=55mm, H=42mm

TECHNICAL SPECIFICATIONS:

- TYPE: UV ELECTRONIC BALLAST/INDUSTRIAL
- BALLAST CONTROLLER IC IS PROGRAMMED TO PROVIDE AUTO PREHEAT, IGNITION & RUN MODE, WHICH ENSURES THE ENHANCED LIFE SPAN OF LAMP/TUBE
- OPERATING VOLTAGE RANGE: $U_n = 170\text{Vac} - 300\text{Vac}$
- MAINS RATED VOLTAGE: $V = 230\text{Vac}$
- MAINS FREQUENCY: $F_n(\text{Hz}) = 50\text{Hz}$
- MAINS I/P CURRENT: $I_n = 550\text{mA}$
- WATTAGE: 120W
- POWER FACTOR: $PF > 0.95$
- SURGE PROTECTION DEVICE: $SPD > 10\text{KV}$
- CREST FACTOR: $CF > 1.70$
- AMBIENT TEMPERATURE: $T_a = 0 \dots 50^\circ\text{C}(\text{max})$, CASE TEMPERATURE: $T_c = 55^\circ\text{C}(\text{max})$
- IN RUSH CURRENT PROTECTION, RFI/EMI PROTECTION



FEATURES:

- SLIM DESIGN
- BODY: METALLIC POWDER COATED
- MAINS LED INDICATOR: RED
- O/P GREEN LED INDICATORS SIGNIFY HEALTHY LAMPS/TUBES

***Due to continuous R&D, design can be changed without prior notification**

***Special Requirements will be entertained**

WORKS/FACORY ADDRESS:

VISION TECH ELECTRONICS

C/9, Bansidher Estate, Bardolepura, opp. Suprabhat Industrial Estate,

O/S Dariyapur Gate, Ahmedabad-380004, Gujarat, India

M: 9925799688, E-mail Id: info@visiontechproducts.com, mukesh@visiontechproducts.com

Web Sites: www.uvballasts.com, www.visiontechproducts.com

www.vision-techs.com, www.visiontechled.com